*Nanotechnology Perceptions*
*ISSN 1660-6795*
*www.nano-ntp.com*

# "Road traffic signs in India are detected and recognized using a Convolutional Neural Network (CNN)"

**Nidhi Gautam[1], Dr. Girdhar Gopal Ladha[2]**

[1]*Research Scholar, Department of Computer Engineering, Sarvepalli, Radhakrishnan University, Bhopal, M.P., India*
[2]*Professor, Department of Information Technology, RKDF Institute of Science & Technology, Bhopal, M.P. India*

A key component of transportation infrastructure, traffic signs are essential for controlling traffic flow, enforcing safe driving practices, and lowering the risk of collisions, injuries, and fatalities. It is essential for an Intelligent Transportation System (ITS) to possess the capacity to recognize traffic signs and automatically detect them in order to be successful. It is essential to identify traffic signs automatically. This is becoming more important as self-driving cars become more common. This work presents a novel deep learning-based approach to Indian traffic sign recognition. A region-based convolutional neural network (CNN) is used in the suggested system to automatically identify and recognize traffic signs. The authors describe various architectural and data augmentation enhancements to the CNN model and take into account unique and challenging Indian traffic sign types that have not been previously discussed in literature. The system is trained and evaluated using a database of real-time images captured on Indian highways. In comparison to the existing method for traffic sign recognition, the experimental results of the proposed methodology show an accuracy of almost 99% for each traffic sign. This accomplishment is essential to reducing the number of accidents and enhancing road safety. Additionally, it provides a strong technical basis for the on-going development of driving assistance for intelligent vehicles.

## 1. Introduction

Roadside signs including speed limits, warnings about nearby children, and impending turns can be read and interpreted by cars thanks to traffic-sign recognition (TSR) technology. Numerous automakers are presently engaged in the development of this technology. Modern cars, trucks, and other vehicles include forward-facing cameras that can be used to study traffic

signs and locate them using image processing techniques. For TSR systems, one of the main uses is speed limitations. The dashboard of a GPS device, however, can also display data gathered from additional speed limit signs. Drivers can be alerted to speed restrictions and traffic signs using this information. Using techniques like picture handling and PC vision, the framework is ready to recognize various traffic signs, enabling it to continuously recognize new ones. The importance of road traffic safety has grown around the world, especially in developed countries, as a result of the rapid speed of innovation and the increase in car ownership. In reality, a considerable number of individuals die in traffic accidents each year, and this number is predicted to keep increasing. [1] The intelligent transport system, which will make driving safer and easier, alert drivers to possible hazards, and help them with navigation and monitoring, must include unconventional driver assistance systems in intelligent vehicles. This kind of organization includes systems such as adaptive cruise control, lane withdrawal warning systems, collision avoidance systems, night vision, traffic sign recognition, and others [2]. Generally speaking, artistic signals like road markings, traffic lights, and signage contain crucial information that drivers need to know about the condition of the traffic. Under favorable circumstances, a number of traits, such as exhaustion, intoxication, and anxiety when driving, can significantly improve human visual perception. An ADAS must be able to interpret this visual language and use traffic sign recognition (TSR) on unlike slants to give drivers the information they need to improve road safety [3]. India has an extensive and impenetrable road system. These roadways' traffic lights assist drivers by directing them toward the best driving choices. The driver receives silent help from these traffic lights. These signs give a general idea of the path that lies ahead. This allows the driver to make more informed decisions about how to drive and what elements to take into account. These signals are typically used to warn drivers of prohibited objects or to assist them in avoiding an unforeseen circumstance. These signs are sometimes rummage-sale-style, designed to incite vehicles to go above the speed limit or other traffic regulations. Every driver on the road must be familiar with all of these signs, and any driver with a charitable driver's license has their familiarity with them confirmed. In order to be easily seen by passing cars, traffic warbles are usually all brightly colored. Since they are all written in a very modest style, even a vehicle moving at a fairly moderate speed may read them with ease. Every driver is expected to pay attention to and obey all traffic signs. Simple, uncomplicated graphical representations are used by traffic signals to show the boundaries and regulations for that specific route segment. Determining demand site management, which is utilized by domestic homes, is the primary objective of the suggested activity. This thesis describes a series of investigations conducted to ascertain how to integrate solar photovoltaic (PV) and advanced metering infrastructure (AMI) on home power distribution systems in order to achieve DSM. Therefore, identifying a more effective AMI design is the first section of this thesis. The design considerations related to integrating solar PVs on a distribution network are examined in the second section. The cost-benefit trade-offs of domestic PV integration in terms of peak demand saving (PDS) and DSM are the main focus of the economic feasibility studies. Additionally, we covered various case studies pertaining to actual implementation problems of advanced metering infrastructure for solar PV systems in this article. In order to execute the suggested DSM solutions, these case studies also address power management.

### 1.1 Current System

One area of object detection that many academics are interested in is traffic sign detection. Traffic signs are designed with exact color and shape criteria, as opposed to general object detection. This facilitates their separation from the background for intelligent robots or humans. Thus, traffic sign detection algorithms usually use either color, form, or both. Unfortunately, because color information cannot be expressed constantly and is not accentuated, shape information is often lost in color images captured by mounted cameras on cars. With modern technology, color information enhancement or shape information enhancement [3] techniques are usually used to manage the preprocess step of a traffic sign.

### 1.2 Indian Traffic Signs

Traffic signs are the noiseless chatterers on the street. Is it the individual overdue the wheel or a unimaginative, having a detailed information about road safety is obligatory for whole previously thumping the streets. Traffic signs stretch information nearby the street environments gaining, proposition instructions to be pursued at the principal crossing or intersections, inform or controller drivers, and sanction proper operational of street traffic. Being unacquainted of street signs is corresponding to chucking attentiveness to the tempest. It can central to penalization of life and property. A person is imaginary to be habituated (get complete an adorned or oral test) with the traffic signs and symbols before locating a driving license in India. Habitually, there are three unalike kinds of street symbols in India.

Figure 1. Road sign categories.

## 2. Related Work

The three phases consist of post-processing, ROI refining and description, and ROI extraction. However, the lengthy post-processing phase was a major flaw in their approach. A critical part of ADAS, the TSDR structure, was the subject of problems with Mammeri et al. (2013) [2]. However, their system only worked within a narrow frequency range and struggled to recognize traffic signs with a lower-resolution camera, as well as camera movements and vibrations. Kim and Lee (2018) According to Cruz Antony Joseph et al. (2024), it is impossible to overstate the significance of object identification and classification in contemporary applications and day-to-day living. Numerous practical applications, including G-lens technology, cancer prediction, optical character recognition (OCR), face recognition, and more, depend on the efficiency of image identification algorithms. Among these, Convolutional Neural Networks (CNN) have emerged as a cutting-edge technique that excels

at feature extraction and offers practical solutions for a variety of object recognition issues. One of CNN's primary advantages is its quicker execution, which makes it particularly helpful for real-time processing. For the creation of practical applications like autonomous driving for vehicles like Tesla and for traffic, the field of traffic sign recognition is crucial. A CNN model was used to achieve a rigorously methodical approach, starting with a rigorous phase of data pre-processing. This preparation step was enhanced by the intentional inclusion of residual blocks during model training, which enhanced the network's ability to extract intricate information from traffic sign images. Interestingly, our proposed methodology yielded an excellent accuracy percentage of 94.25%, demonstrating the system's strength and capability in object recognition. The considerable improvements we have achieved in certain indicators over earlier approaches demonstrate the special potential of our strategy. Our approach offers a productive technique to extract features, excels in accuracy, and takes advantage of CNN's quick execution speed. Purohit Richa et al. (2023) A key component of traffic management and driver discipline, traffic sign recognition (TSR) lowers the risk of crashes, property damage, fatalities, and injuries. Automatic traffic sign detection and identification are key components of any Smart Transportation System (STS). In the era of driverless cars, automated traffic sign recognition and identification is crucial. This study looks at an Indian self-directed traffic sign detection system that uses deep learning. The automatic identification and recognition of traffic signs was developed from the ground up using convolutional neural networks (CNNs). Deep convolutional neural networks are currently being used in an increasing number of object recognition applications. Convolutional neural networks, or CNNs, have transformed both due to their superior performance and high detection rate. In this paper, a deep convolution neural network-based method for identifying traffic signals is proposed. Several CNN designs are compared with each other in this study. A popular machine learning framework for training deep neural networks, TensorFlow, is built on the massively parallel multithreaded programming of CUDA architecture. The effectiveness of the created computer vision system was validated by the experiment results. The proposed model outperforms the existing traffic sign detection approach with an accuracy of 97.08%. The low real-time performance of deep learning-based traffic sign recognition techniques and the ease with which the environment can affect traditional traffic sign detection are two problems that the enhanced traffic sign detection and recognition algorithm for intelligent vehicles, proposed by Jingwei Cao et al. (2019), seeks to address. Initially, the hue HSV Traffic sign detection is made effective by the shape attributes and spatial threshold segmentation, which takes advantage of space. Second, the model is made much better than the standard Le Net 5 convolutional neural network model by using the Adam method as the optimizer algorithm, starting with the Gabor kernel as the first convolutional kernel, and adding the batch normalization processing after the pooling layer. In conclusion, based on the German traffic sign, the travel. According to the contribution of Alexander Hanel et al. (2018), the selected datasets are compared in terms of their usefulness for traffic sign detection. The comparison includes the process of producing synthetic images, the virtual environments needed to produce them, and their environmental conditions. Both the labeling methods used on the datasets and variations in the appearance of traffic signs are compared. A deep learning traffic sign detector is developed using numerous training datasets with different proportions of synthetic and actual training samples in order to evaluate the synthetic SYNTHIA dataset. According to test done exclusively on synthetic samples, the detector can achieve an overall

accuracy and ROC AUC of more than 95% for both a small rate and a big rate. Faming Shao et al. (2018) introduced a novel approach for real-time traffic sign identification and recognition in a real-world traffic situation. Based on databases of traffic signs from China and Germany, the experimental results showed that the proposed method outperformed the state-of-the-art approach, improved the overall processing efficiency of the detection and classification process, and met real-time processing requirements. [9] A list of some innovative and successful traffic identification and sign classification techniques was presented by Yassmina Saadna and Ali Behloul (2017). Actually, the main goal of detection techniques is to locate zones of interest using traffic indicators. We divide detection methods into three primary categories: learning-based (including deep learning), shape-based, and color-based (based on color space classification). Additionally, we divide classification methods into two categories: learning methods based on hand-crafted features (HOG, LBP, SIFT, SURF, and BRISK) and deep learning techniques. For ease of access, the several datasets as well as detection and classification methods are gathered in tables. Future research directions and recommendations are also given to enhance TSR's performance. [13] Canan Tastimur et al. (2016) state that image processing techniques are used to detect traffic signs, and fuzzy integrals are used to recognize them. FuzzyIntegral's use of positive algorithmic elements as input parameters in traffic sign recognition systems leads in lower computational costs and improved recognition accuracy rates. The experimental findings show that the proposed method yields very accurate results in a reasonable length of time. [14] The efficient survey of traffic signs was encouraged by Q. Yao et al. (2016) in order to map the road network and the roadside scenery. A drawing method is proposed to quickly approximate the traffic sign perimeter, which is inspired by the human demarcation of traffic signs. The speed limit sign circular and the most popular traffic sign color model are both examined in this study. The edge anchorpoints of traffic signs are located at the local maxima of hue and gradient difference. Beginning with the anchor points, the traffic sign's shape is ingeniously drawn along the most crucial direction of color and intensity uniformity. A traffic sign's rare occurrence is then automatically and statistically determined to be the temporally salient one. In order to rapidly, affordably, and effectively construct a traffic sign infrastructure database that could be linked to Google Maps, Victor J. D. Tsai et al. (2016) set out to develop techniques for finding, recognizing, and extracting traffic signs from Google Street View (GSV) images along user-selected routes. The framework and tactics used in the proposed system are described.[11] Safat B. Wali et al. (2015) developed an efficient TSDR system that incorporates an improved dataset of Malaysian traffic signs. The developed method features a low false positive rate and a short calculation time. It is unaffected by variations in illumination, translation, rotation, and viewing angle. The system is being developed in three stages: picture preprocessing, detection, and recognition. For system demonstration, an RGB color segmentation and shape matching system with an SVM classifier yielded promising results with respect to processing time (0.43 s), false positive rate (0.9%), and accuracy (95.71%). The area under the receiver operating characteristic (ROC) curves was introduced to quantitatively evaluate the recognition performance. The suggested system has a quick processing time and a comparatively good accuracy. Two different methods for recognizing and detecting traffic signals based on their color and shape were presented by Manjare and Hambarde (2014). The first method is to fit a Gielis curve. This technique applies an algorithm to a variety of shapes, such as circular, triangular, and octagonal ones. Fitting contour points

into a Gielis curve takes a long time, which is clearly not acceptable in a real-time system. Therefore, in order to decrease processing time, more research and development are required. It recognizes traffic signs with an accuracy of 85%. The second strategy is based on neural networks. Neural network stages were used to identify traffic sign patterns. The first step is to reduce the number of MLP inputs by preprocessing the image of the traffic sign. It makes sense that the visual attention mechanism was proposed by Xiaoguang HU et al. (2012) as a means of recognizing traffic signs. Our technology initially analyzes the whole image using a visual attention model to predict potential locations for traffic signs. These qualifying locations will next be analyzed in line with the sign's shape characteristics in order to detect traffic signs. Based on the results of traffic sign detection experiments, the proposed method is more successful and dependable than other saliency detection systems currently in use. [10]

## 3. Materials and methods

### 3.1 Datasets

Data collecting is an important part of the project in its early phases. Pre-processed images of different traffic signs were taken from Kaggle. This collection contains a wide range of image sets and types. To produce distinct and customized training images, image augmentation techniques were used with pre-existing training data. These methods, which aid in avoiding the model from fitting too closely, include rotation, cropping, cushioning, and horizontal flipping. The dataset included about 40,000 photos after augmentation. After the gathered data was combined, a special dataset known as the "Traffic sign dataset" was released to the public on Kaggle. After that, the dataset was split into three parts: 70% for training the model that will be used for classification, 15% for testing, and 15% for validation. By ensuring that there is a sufficient amount of data available for training, this division produces a model that is more accurate. Each class used a total of 1000 photos, of which 800 were used for training and 100 for testing and validation.

### 3.2 Neural Networks with Convolutions

One well-liked deep learning model that is well known for its efficacy is the convolutional neural network (CNN). This kind of algorithm is widely used to address problems pertaining to image classification and is becoming more and more popular in a variety of industries, including music and health. Fully-connected layers, convolutional layers, and pooling layers are some of the interdependent layers that make up the CNN model. These layers employ the backpropagation technique to dynamically learn the data topologies.

### 3.3 The layer of convolution

One of the most important components of a CNN is the convolution layer. By applying a channel to an info, all field information is solidified into the single pixels and the picture's size is reduced. A image complexity that recognizes an object's edges is displayed in Figure 2.

### 3.4 The Layer of pooling

A pooling layer is used to reduce the size of an image that is used as a convolutional layer contribution. As a result, the network has to do less computation and learn fewer features. There are various types of pooling layers, including average pooling layers, global pooling

layers, and maximum pooling layers. Maximum pooling is used in this investigation. The greatest pooling layer shrinks the image's size, as seen in Figure 2.




Figure 2. Layer of pooling

3.5 Function of Activation

An activation function is a non-linear modification that determines whether a neuron is activated before moving on to the layer of neurons below. In this instance, the Rectified Linear Unit (ReLU) is the activation function that is employed.

## 4. The suggested model

There are multiple modules in the suggested work. Initially, input photos are supplied. The region of interest in the suggested CNN model is then determined by calculating the shape detection on the color probability of the convolutional model. The convolutional neural networks' layers serve as the foundation for this. Data augmentation and object detection are then put into practice. This is the detailed process that the project is expected to follow. (Figure 3)




Figure 3. CNN framework.

4.1. Resnet50

One MaxPool layer, one Normal Pool layer, and forty-eight Convolution layers make up the ResNet50 model. It includes floating point operations (3.8 x 10^9). It was the ResNet model's standard variant. The top-1 error rate of 20.45 percent and the top-5 error rate of 5.26 percent are both attained by the ResNet 50 model. It refers to a single model with 50 layers, not a collection of them. These designs could be applied to computer vision tasks such as object detection, object recognition, and image categorization. In order to take advantage of its depth and reduce processing, it can also be applied to jobs that are not related to computer vision. The ResNet50's design is seen in Figure 4.




Figure 4. Resnet50 architecture

4.2. Inception V3

On ImageNet datasets, the picture identification model Inception V3 has shown an accuracy of 78.1 percent. Using the picture-Net dataset, it was discovered that the Inception V3 picture model identification achieved over 78.2% accuracy. There are 42 layers in the Inception V3 model, which includes a few additional V1 and V2 models. Despite this, a model's efficacy is astounding. The Inception V3 model's architecture is shown in Figure 5.




Figure 5. InceptionV3 architecture.

## 5. Findings and conversation

Table 1 displays the accuracy and loss for the training and validation datasets for the VGG19 Model. This model was trained over 25 epochs with a learning rate of 0.01. The accuracy and loss of the VGG19 Model for the training and validation datasets are shown in Table 1. This model underwent 25 training iterations with a learning rate of around 0.01 and produced a training accuracy of 95.58%. The table shows that the validation loss will grow in comparison to the first epoch as training accuracy rises. Using the test dataset, the model's accuracy was evaluated and found to be 88.36%. In contrast, the RESNET50 model performed better with 25 epochs and a learning rate for 25 epochs of 0.01; it achieved a training 98.63% training accuracy. These results are shown in Table 2. The model's test accuracy on the test dataset was 87.82%. The performance of the InceptionV3 model is shown in Table 3. It was trained over 25 epochs with a learning rate of 0.01 for each epoch, and it had a training accuracy of 98.20%. The precision of the model's testing was 88.93%. Table 4 displays the results for the EfficientNetB4 model, which performed better than the other models with a test accuracy of 91.95 present.

Table 1. Performance of VGG19 model.

| Epoch | Training Loss | Training Accuracy | Validation Loss | Validation Accuracy |
|---|---|---|---|---|
| 1 | 1.7765 | 0.3320 | 1.1643 | 0.4817 |
| 5 | 0.6367 | 0.7346 | 0.6324 | 0.7429 |
| 10 | 0.3749 | 0.8389 | 0.4420 | 0.8138 |
| 15 | 0.2817 | 0.8745 | 0.3673 | 0.8586 |
| 20 | 0.1895 | 0.9291 | 0.3698 | 0.8663 |
| 25 | 0.1325 | 0.9518 | 0.3077 | 0.8912 |

**Table 2.** Resnet50 performance.

| Epoch | Training Loss | Training Accuracy | Validation Loss | Validation Accuracy |
|---|---|---|---|---|
| 1 | 1.872 | 0.6809 | 0.6390 | 0.7569 |
| 5 | 0.1981 | 0.9185 | 0.3474 | 0.8652 |
| 10 | 0.0995 | 0.9710 | 0.3795 | 0.8853 |
| 15 | 0.0396 | 0.9851 | 0.3471 | 0.9366 |
| 20 | 0.0348 | 0.9863 | 0.4201 | 0.8888 |

**Table 3.** Inceptionv3- performance.

| Epoch | Training Loss | Training Accuracy | Validation Loss | Validation Accuracy |
|---|---|---|---|---|
| 1 | 0.986 | 0.633 | 0.510 | 0.784 |
| 5 | 0.246 | 0.900 | 0.301 | 0.888 |
| 10 | 0.096 | 0.961 | 0.284 | 0.904 |
| 15 | 0.041 | 0.986 | 0.358 | 0.908 |
| 20 | 0.048 | 0.982 | 0.337 | 0.903 |

**Table 4.** Performance of efficientnetb4 model.

| Epoch | Training Loss | Training Accuracy | Validation Loss | Validation Accuracy |
|---|---|---|---|---|
| 1 | 0.9329 | 0.6421 | 0.5024 | 0.7950 |
| 5 | 0.2698 | 0.8986 | 0.2610 | 0.8829 |
| 10 | 0.1259 | 0.9512 | 0.2282 | 0.9147 |
| 14 | 0.0646 | 0.9732 | 0.2420 | 0.9250 |
| 15 | 0.0569 | 0.9790 | 0.2557 | 0.9299 |

## 6. Conclusion

This research proposed a practical deep learning method for road traffic sign picture identification and recognition that worked well in a variety of scenarios, such as variations in scale, direction, and illumination. The project presents CNN, which integrates the latest developments in design, data augmentation, and parametrical values. A state-of-the-art customized dataset was obtained in real time for the training and validation of the proposed CNN model. ResNet-50 is a convolutional brain network with 50 layers that is utilized for efficient output in addition to data augmentation. It prepares more than 1,000,000 images from the Image Net data set by stacking the pretrained version of the organization. Pictures can be ordered into the 1000 item classification by the organization. The InceptionV3 model receives the images. The 42 layers in this Commencement V3 model are a few more than those in the V1 and V2 versions.The reported performance gains were clearly true, as seen by the decline in both the miss-rate and false-positive rates.

## References

1. B. R. Litman & H. Ahn. (1998). Predicting financial success of motion pictures. In B. R. Litman (Ed.), the motion picture mega-industry. Boston, MA: Allyn & Bacon Publishing, Inc
2. Kumar and Kumar, “Predicting Movie Success or Failure using Linear Regression & SVM over Map- Reduce in Hadoop”, International Journal of Innovative Research in Computer and

Communication Engineering, Vol. 6, Issue 6, June 2018.
3. "Prediction of Movies popularity Using Machine Learning Techniques", International Journal of Computer Science and Network Security, VOL.16 No.8, August 2016, pp 127-131.
4. Chaudhari et al., "A Data Mining Approach to Language Success Prediction of A Feature Film", International Journal of Engineering Sciences & Management Research, 2016, pp. 1-9.
5. Meenakshi et al., "A Data mining Technique for Analyzing and Predicting the success of Movie", Journal of Physics: Conf. Series 1000 (2018) 012100 doi: 10.1088/1742-6596/1000/1/0100. Pp 1-9.
6. Quader et al., "A Machine Learning Approach to Predict Movie Box-Office Success", 20th International Conference of Computer and Information Technology (ICCIT), 22-24 December, 2017.
7. G. Diamantopoulos and M. Spann 2005 Performance analysis of CART and C5.0 using sampling techniques Advances in Computer Applications. 11 3, pp. 233– 243.
8. https://www.edureka.co/blog/what-is-machine- learning/
9. Christopher M. Bishop, "Pattern Recognition and Machine Learning (Information Science and Statistics)", 2006. Page-3
10. Russel, "Artificial Intelligence: A Modern Approach",January 1, 2015
11. Hastie et al. "The Elements of Statistical Learning: Data Mining, Inference, and Prediction", Second Edition (Springer Series in Statistics), 2016, pp. 28. [Online]. Available: https://www.amazon.com/ElementsStatistical- Learning-Prediction-Statistics.
12. Richard S. Sutton et al., "Reinforcement Learning: An Introduction (Adaptive Computation and Machine Learning", 2018, second edition, pp.-2. [Online]. Available: https://www.amazon.com/ReinforcementLearning-Introduction-Adaptive-Computation.
13. Smola and S. Vishwanathan, Introduction to Machine Learning. United Kingdom at the University Press, Cambridge, October 1, 2010.
14. [Online]. Available: www.analyticsvidhya.com.Sunpreet Kaur, Sonika Jindal "A Survey on Machine Learning Algorithms", International Journal of Innovative Research in Advanced Engineering (IJIRAE) 2016, Issue 11, Volume 3.
15. W. Gerstner, "Supervised learning for neural networks:a tutorial with JAAv exercises".
16. O. R.S. P. breiman L, friedman J.H., "Classification and regression trees." Belmont CA Wadsworth International group, 1984. B. C. U. P.E.tgoff, "Multivariate decision trees: machine learning," no. 19, 1995, pp. 45–47
17. Richa Purohit et al. Insights of Deep Convolutional Neural Network for Traffic Sign Detection in Autonomous Vehicle, 2023 2nd International Conference on Applied Artificial Intelligence and Computing (ICAAIC) 2023, IEEE
18. J Cruz Antony et al. Traffic sign recognition using CNN and Res-Net, February 2024 EAI Endorsed Transactions on Internet of Things, DOI: 10.4108/etiot.5098